

# ISOLI

## CLAIER

# PT 140

کلایر، نماینده انحصاری ایزولی در ایران



Altezza max. di lavoro  
Max. Working height  
Max. Arbeitshöhe

14 m

Sbraccio max. di lavoro  
Max. Working boom extension  
Max. Arbeitsaulandung

8,7 m R+A

Portata  
Capacity  
Tragfähigkeit

max 250 kg  
in funzione della configurazione della PLE  
It depends on MEWP configuration

N° operatori  
N° operators  
N° de Arbeiter

2

Forza manuale max.  
Max. manual force  
Max. Handkraft

40 daN

Velocità max. vento  
Max. wind speed  
Max. Windgeschwindigkeit

12.5 m/s

Braccio di lavoro  
Working boom  
Arbeitsarm

Braccio telescopico a 2 sezioni  
Telescopic end 2 section element

Angolo braccio  
Boom angle  
Armwinkel

-24°/+76°

Rotazione sovrastruttura  
Upperstructure rotation

400°

Piattaforma  
Platform  
Hubarbeitsbühne

Alluminio 1390x715x1115 mm  
Alluminium 1390x715x1115 mm

Rotazione piattaforma  
Platform rotation  
Drehung des Hubarbeitsbühne

Idraulica 90°dx+ 90°sx  
Hydraulic 90°RH+ 90°LH

Livellamento piattaforma  
Platform levelling  
Nivellierung der Hubarbeitsbühne

Idraulico  
Hydraulic

Stabilizzatori  
Outriggers  
Abstützungen

Idraulici, rovesciabili ant./ inclinati post.  
Hydraulic, tipping at front, "A" type at rear

Scartamento minimo stab.  
Outriggers minimum width  
Spurweite Abstützungen min./max  
Anteriore 3.05 m - Posteriore 2.32 m  
Front 3.05 m - Rear 2.32 m

Comandi  
Controls  
Steuerungen  
Idraulici  
Hydraulic

Installazione minima  
Minimum installation  
Mindeste Installation  
MTT 3.5 t  
TWG 3.5 t

DIAGRAMMA DI LAVORO  
WORKING DIAGRAM

METRI  
METERS

